

FAUST LACK GL



DESCRIPTION

Wood and metal water based paint with the innovative and ecological formula Wasser Protect.

PRODUCT PROPERTIES

- Superior whiteness
- Perfect surface
- Excellent coverage
- Perfect workability and levelling
- Contains anti yellowing additive
- It is available in 4 basis W, P, D and TR
- Can be pigmented according to DCTS system
- Very strong adhesion and rapid drying

RECOMMENDATIONS FOR USE

It is recommended to be used as a paint on all metal surfaces that are intended for indoor and outdoor use. It is used for painting metal constructions that are intended for use, such as workshops stairs, handrails, metal gates, etc. It is used for painting the fences made of wooden lath, wooden stairs, wooden handrails, etc.

TECHNICAL DATA

Resin	Alkyd resin
Density EN ISO 2811-1	1,20±0,02 gr/ml
Dry residue EN ISO 3251	62%
Dilution degree	10 – 20%
Viscosity	115 ± 5 KU
Drying time	2 - 3 hrs Also depending on environment conditions and diluent used
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m³)	≥ 0.5

APPLICATION GUIDELINES

- Application method: Brush, roller and spray gun.
- Thinning: With clean water 10-20%

SURFACE PREPARATION

Clean the surfaces of the damaged old paint without seams and the rusted parts by grinding the surface. By washing process, eliminate all the dust generated by the grinding process as well as other elements that hinder adhesion such as grease, oils, etc. Later, apply Metal Haftgrund 550 liner or Faust Primer (wood) liner. After complete drying, apply Faust Lack GL liner. Wood surfaces should be free from high moisture content, free from dust and elements that hinder the adhesion of the paint. In cases where it is applied on wooden surfaces, it is recommended to use Faust Primer.

PRODUCT PREPARATION

Initially, dilute the product using the appropriate quantity up to the suitable application viscosity. It is recommended that the water mixture be made using an electric mixer.

APPLICATION OF PRODUCT

Application of product Alpen Lack GL is made by air pistol, brush or roller. First, pour the prepared product into the container. Then, with the pistol, the product is spread on the metal surface. The application is done by applying two consecutive coatings in order to achieve the best coverage surface. Make sure that the appropriate thickness of the coating is obtained in order to achieve maximum metal protection. Clean the working tools with running water immediately after use.

PACKAGING

0.75 lt

STORAGE

36 months, provided that the cans are closed and in normal storage conditions.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- It is recommended not to make application of product in temperatures below 5°C.
- Faust Lack GL basis are used only to produce colour nuances through the DCTS system

