

FLIESEN FARBE F20



DESCRIPTION

Premium quality acrylic paint, with high resistance to different weather conditions, acrylic emulsion-based.

PRODUCT PROPERTIES

- Strong bonding
- Good workability
- Available in reddish colour
- Long term colour durability
- Weather conditions resistant

RECOMMENDATIONS FOR USE

Premium quality acrylic paint, with high resistance to different weather conditions, acrylic emulsion-based.

SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the paint. Repair all cracks and damaged parts and then, it is recommended to apply the Macht Tiefgrund Wasser liner, diluted with 1:1 water. When applying the liner, avoid creating a film, which then creates problems in gluing the paint to the support.

TECHNICAL DATA

Resin	Acrylic copolymer
Density EN ISO 2811- 1	1,45±0,02 gr/ml
Dry residue EN ISO 3251	65%
Dilution degree	10 – 15%
Viscosity	110 ± 5 KU
Drying time between two coatings	4 - 6 hours
VOC in the ready product (European Directive 2004/42/CE) (g/l)	≤ 10
TVOC ambient emissions, Simulation chamber ISO 16000- 9 (mg/m ³)	≤ 0.2
Covering ability EN ISO 6504- 3	≥ 99.5% Class I
Washing resistance ISO 11998	Class I

APPLICATION OF PRODUCT

Application of product Fliesen Farbe F20 is applied by brush or roller. The application cycle includes at least the application 1 coating of paint. Clean brushes, rollers and other working tools with water before the paint dries.

PACKAGING

Plastic container 3lt/10lt

STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

NOTES

- In new concrete surfaces the product is recommended to be used at least after approx. 30-40 days.

CONSUMPTION

9 - 10 m² / lt (two coats)

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

