



OFF FARBE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

OFF FARBE: Paint remover

Free from methylene chloride
Paint remover for interior and exterior use

RECOMMENDED USES

OFF FARBE Suitable for removing old layers from painted surfaces.

TECHNICAL CHARACTERISTICS

Density	1,02±0,02 gr/ml
Production viscosity Storage viscosity	50±5 KU 23°C 50±5 KU 23°C
Spreading rate	Up to 5 m²/L
Drying time	20 ± 5 minutes (Drying and recoating time may be extended under low temperature and high relative humidity conditions)
Color	Transparent
VOC (Volatile Organic Compounds)	EU limit value for this product, Category A/d Interior/exterior trim varnishes and woodstains, including opaque woodstains: 130 g/l (2010). This product contains a maximum of 95 g/l VOC.

APPLICATION INSTRUCTIONS

Application method: Brush, roller
Diluent: Ready to use
Thinner: N.A

Apply OFF FARBE to the surface. It needs 10–20 minutes to penetrate properly into the old paint. After that, the paint should start to come off. Repeat the application if the result is not effective. In the case of old paints and varnishes (especially two-component systems), apply the remover in an even layer and leave it for a longer time and/or combine with mechanical removal using a spatula or scraper. After use, rinse with water and let it dry before repainting.

Tools should be cleaned with soap and water immediately after application.

PACKAGING

750 ml

STORAGE

24 months, provided that the containers are sealed and stored under normal storage conditions.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Refer to the labeling mentioned on the container. If more information is needed, consult the material safety data sheet (MSDS).

NOTES

Remove as much product as possible from brushes and rollers before washing

Clean brushes and rollers with water and detergent solution after use

