

## SPACHTEL FINISH



### DESCRIPTION

Cement based grout made up of filler with selected granulometry and special additives for indoor use

### PRODUCT PROPERTIES

- Does not create cracks
- Strong bonding
- White colour
- Final smooth finish
- Easy application and grinding
- Does not shrink even with thick film

### RECOMMENDATIONS FOR USE

It is used for wall polishing on all the interior dwelling spaces where we want to create a smooth and fair surface for painting inner wall surfaces, used for rendering the interior of the ceiling, concrete surfaces in the interior, room, kitchen, toilette surfaces, etc.

### TECHNICAL DATA

Basis	Acrylic copolymer
Density EN ISO 2811-1	1,75±0,02 gr/ml
Dry residue EN ISO 3251	80%
Mixing ratio	Ready for use
Colour	White
Tensile adhesion strength in concrete	≥ 0,8 N/mm <sup>2</sup>
Consumption:	
Structure 1.5mm complete	2.5-3.0 Kg/m <sup>2</sup>
Structure 2mm complete	3.0-3.5 Kg/m <sup>2</sup>
Structure 2mm complete	3.5-4.0 Kg/m <sup>2</sup>
Structure 3mm complete	4.5-5.0 Kg/m <sup>2</sup>
Drying time	24 hours
Resistance to humidity	W1

## APPLICATION GUIDELINES

- Application method: Spachtel Finish can be applied through a spatula.
- Thinning: 5 liters of water / 15 kg

## SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the product.

## PRODUCT PREPARATION

Fill a container with the required amount of water and then add a Spachtel Finish product in a mixture with an electric mixer. Mix the product until a homogeneous mass without grains that make application difficult is obtained.

## APPLICATION OF PRODUCT

Application of product Spachtel Finish is done with a metal notched trowel. Spread the product on the surface to be rendered and bring it to the required thickness. The application thickness of a coating shall not exceed 3 mm. The product must be applied in two coatings. Clean the spatula and other working tools with water immediately after application.

## PACKAGING

15 kg

## STORAGE

12 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

## HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

## NOTES

- In fresh concrete surfaces the product should be applied at least after 30-40 days.
- It is recommended to avoid application of product at temperatures below 5°C.

