

## SPACHTEL MASSEN



### DESCRIPTION

Cement based grout made up of filler with selected granulometry and special additives for indoor and outdoor use

### PRODUCT PROPERTIES

- Does not create cracks
- Strong bonding
- White colour
- Final smooth finish
- Easy application and grinding
- Does not shrink even with thick film

### RECOMMENDATIONS FOR USE

It is used for wall polishing on all the interior dwelling spaces where we want to create a smooth and fair surface for painting inner wall surfaces, used for rendering the interior of the ceiling, used for rendering of concrete surfaces in the interior. It is used for rendering the surfaces of exterior façades.

### TECHNICAL DATA

Basis	Cement
Density EN ISO 2811-1	1,45±0,02 gr/ml
Dry residue EN ISO 3251	100%
Mixing ratio	32±1%
Colour	White
Tensile adhesion strength in concrete	≥ 0,8 N/mm <sup>2</sup>
Consumption	1 Kg/m <sup>2</sup>
Drying time between two coatings	2 – 4 hours
Drying time for grinding	24 hours
Drying time for painting	72 hours
Compressive strength	≥ 5 N/mm <sup>2</sup> (CS III)

## APPLICATION GUIDELINES

- Application method: Spachtel Massen can be applied through a spatula
- Thinning: 6.5 liters of water / 20 kg

## SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the product.

## PRODUCT PREPARATION

Fill a container with the required amount of water and then add a Spachtel Massen product in a mixture with an electric mixer. Mix the product until a homogeneous mass without grains that make application difficult is obtained.

## APPLICATION OF PRODUCT

Application of product Spachtel Massen is done with a metal notched trowel. Spread the product on the surface to be rendered and bring it to the required thickness. The application thickness of a coating shall not exceed 3 mm. The product must be applied in two coatings. Clean the spatula and other working tools with water immediately after application.

## PACKAGING

10 kg, 20 kg

## STORAGE

12 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

## HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

## NOTES

- In fresh concrete surfaces the product should be applied at least after 30-40 days.
- It is recommended to avoid application of product at temperatures below 5°C.

