
DEUTSCH COLOR

CREAZIONI





It is a decorative paint that gives a sand effect in silver and golden colors.

CHARACTERISTICS

- Strong bonding
 Variety of structures
 Indoor application
 Application on existing paints
 Very easy to be applied
- Brilliant colours with durability

RECOMMENDATIONS FOR USE

It is used in all those surfaces where a decorative effect on indoor walls is desired.

TECHNICAL DATA	
Resin	Acrylic copolymer
Density EN ISO 2811-1	1,25±0,02 gr/ml
Dry residue EN ISO 3251	55%
Dilution degree	Ready for use
Viscosity	115 ± 5 KU
Drying time between two coatings	4 - 6 hours
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m³)	≤ 0.2
Covering ability EN ISO 6504- 3:	≥ 98% Class II
Washing resistance ISO 11998:	Class I

DEUTSCH COLOR

SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the paint. Repair all cracks and damaged parts using the line products of Deutschcolor, Vox 707, Glatte Spachtel, Spachtel Finish, etc. Then, it is recommended to apply the Macht Tiefgrund Wasser liner, diluted with 1:1 water of Macht Haftgrund liner diluted with water in 1:3 ratio, then the final surface on which Creazioni is applied must be painted with premium quality paints such as Picasso Classic VN-35, Picasso Master, etc.

PRODUCT PREPARATION

First, mix well and homogenize the product, then begin with the application. Use a low speed electric mixer to make a mixture as uniform and complete as possible.

APPLICATION OF PRODUCT

The product Creazioni is applied by a brush or roller. The application cycle includes at least the application of one coating of paint. Clean brushes, rollers and other working tools with water before the paint dries.

PACKAGING

1lt / 3lt plastic buckets

CONSUMPTION

10 - 12 m² / It

STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- In fresh concrete surfaces, the product should be applied at least after 30-40 days.
- It is recommended to avoid the application of the product at temperatures below 5°C.





