

MEGAGRUND



DESCRIPTION

High quality liner with acrylic emulsion base and selected granulometry aggregates

PRODUCT PROPERTIES

It creates coarse surface

- Good substrate bonding
- Promotes bonding with decorative grout
- Prolongs drying time with decorative grout
- Provides colour uniformity in decorative grout
- Different nuances according to DCTS colour system

RECOMMENDATIONS FOR USE

It can be used in all indoor and outdoor, new and old walls. It is used as bonding liner before the scratching plaster in thermal insulation systems, in plastered wall systems, in old painted plastered wall systems.

TECHNICAL DATA

Resin	Acrylic copolymer
Density EN ISO 2811-1	1,35±0,02 gr/ml
Dry residue EN ISO 3251	50%
Dilution degree	10 – 30%
Viscosity	115 ± 5 KU
Drying time between two coatings	2 - 4 hours
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m3)	≤ 0.2

APPLICATION GUIDELINES

- Application method: Brush or a roller.
- Thinning: It is recommended to be diluted 10-30% with water.

SURFACE PREPARATION

The surfaces should be free completely dry, clean and free from dust and elements that hinder the adhesion of the product.

PRODUCT PREPARATION

Dilute the product Megagrund with 10-30% water, ensuring that it is fully mixed with the liner. Use a low speed electric mixer to make a mixture as uniform and complete as possible.

APPLICATION OF PRODUCT

Product Application Megagrund is applied by brush or roller. The application cycle includes at least the application 1 coating of liner. The time needed between the liner coating and scratched plaster coating is 2-4 hours depending on weather conditions, temperature and humidity. When applying the liner, avoid creating a film, which then creates problems in gluing Scratched plaster to the support. Clean brushes, rollers and other working tools with water before the paint dries.

PACKAGING

3 lt, 5 kg

STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C dhe +30°C. Protect it from frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

