

PICASSO CLASSIC MOLD PROTECT



DESCRIPTION

Premium quality plastic paint, high resistance to continuous washing and fungus, with emulsion-based PVA-VEOVA.

PRODUCT PROPERTIES

- Finished surface matt
- Excellent coverage
- It is available in 4 basis W, P, D and TR
- Equipped with antibacterial certificate
- Very good workability and levelling
- Very strong adhesion and rapid drying
- Prevents growth of fungus and micro-organisms
- Supports 3200 washing cycles 30 days after application

RECOMMENDATIONS FOR USE

Recommendations for use It is used in all interior, new, old and painted walls and ceilings, previously painted with cement base paint, lime, gypsum, and any kind of indoor space, bedrooms, toilets, living rooms, office spaces, services etc.. It is widely used in areas where there are high levels of humidity.

TECHNICAL DATA

Resin	PVA VEOVA Polymer
Density EN ISO 2811-1	1,45±0,02 gr/ml
Dry residue EN ISO 3251	65%
Dilution degree	10 – 15%
Viscosity	110 ± 5 KU
Drying time between two coatings	2 - 4 hours
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m3)	≤ 0.2
Covering ability EN ISO 6504-3	≥ 98% Class II
Washing resistance ISO 11998	Class I

SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the paint. Repair all cracks and damaged parts using the line products of Deutschcolor, Vox 707, Glatte Spachtel, Spachtel Finish, etc. Then, apply Reninger 42 and leave it to operate. Clean the surface with water after 30 minutes. Apply a second coat of Reninger 42 by brush or roller, and leave it to operate for 24 hours. After the surface has dried fully, apply the Macht Tiefgrund Wasser liner, diluted with water in 1:1 ratio. When applying the liner, avoid creating a film, which then creates problems connecting the paint to the support.

PRODUCT PREPARATION

Dilute the product Schimmel Stopen 990 with 10-15% water, except for bases D and TR which are recommended to be diluted with not more than 5% water. Use a low speed electric mixer to make a mixture as uniform and complete as possible.

APPLICATION OF PRODUCT

Application of the product Picasso Classic Mold Protect is made with a brush or roller. The application cycle includes at least the application of two coatings of paint. The time needed between the two coatings is 2-4 hours depending on weather conditions, temperature and humidity. Clean brushes, rollers and other working tools with water before the paint dries.

PACKAGING

3lt / 10lt plastic buckets

STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- It is recommended not to wash the painted surfaces until 20-30 days after application.
- In fresh concrete surfaces the product should be applied at least after 30-40 days.

