

CREATIVE PUTZ 1. 2. 3.



DESCRIPTION

Decorative coating that serves for the treatment of facades and indoor surfaces.

PRODUCT CLASSIFICATION

Creative Putz 1.2.3 is classified according to EN 998 - 1.

CHARACTERISTICS

- For indoor and outdoor use.
- High resistance to weather conditions.
- Good workability.
- Forms a stable and long-lasting structure.

RECOMMENDATIONS FOR USE

Creative Putz 1.2.3 is suitable to create decorative coatings with excellent waterproof, adhesive and elastic qualities. It is also used to create decorative coatings on surfaces filled with cement mortar or basic thermal insulating mortar, which have been flattened beforehand with MEGAGRUND or one product from the TB 400 / TB 800 line of products. It is also used in outdoor thermal insulation systems as a decorative coating.

TECHNICAL DATA

Base:	Cement Powder
Form:	Pasty
Color:	White
Density:	1,80±0,02 gr/ml
Consumption:	
Structure 1.0 mm:	2.2 - 2.5 kg/m ²
Structure 1.5 mm:	2.5 - 3.0 kg/m ²
Structure 2.0 mm:	3.2 - 3.5 kg/m ²
Structure 3.0 mm:	4.0 - 4.5 kg/m ²
Touch drying time:	2 hour
Drying time:	24 hours (Drying may be prolonged under conditions of low temperature and high relative humidity)
Adhesion strength:	≥ 0.5 MPa
Flexural strength:	500 N
VOC (Volatile Organic Compounds):	Limit value for this product Category A/a "Interior matt walls and ceilings (Gloss<25@60°)": 30g/l (2010). The product contains max. 29g/l.

SURFACE PREPARATION

The medium in which the product will be applied must be cleaned in advance from dust, oils, paints, wax residues, and anti-adhesive materials. There cleaning of oils, paints, waxes or anti-adhesive materials is done mechanically or manually. Before applying Creative Putz 1.2.3, the medium must be leveled and flattened with the dry Mineral Megaground primer. The mediums must be flat and mechanically stable, in purpose of use.

APPLICATION OF PRODUCT

Creative Putz 1.2.3 is applied through a straight, metallic screed directly on the surface which has been pre-treated with MEGAGRUND LIQUID primer. After putting the product on the support, rub it with a plastic screed, to create the structures you wish.

STORAGE

12 months after manufacture date, if stored in original and unopened packaging and protected from direct exposure to sun and frost.

CONSUMPTION

2.5- 5 Kg/m² depends on grain size

PACKAGING

25 Kg paper bags

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

