

FLUIDCRET G



DESCRIPTION

Concrete drying retardant. Reducer of the amount of water, and plasticizer.

CHARACTERISTICS

Plasticizer, Type A - additive for waterproofing in concrete preparation. Fluidcret G is a liquid additive that acts as a plasticizer and waterproofing agent in concrete, thus offering the following advantages:

- Significantly increases water impermeability in positive and negative pressure or capillary absorption.
- Improves workability without the need to increase the amount of water.
- Eliminates the air within the concrete mass.
- Does not contain chlorides and other irritating agents.
- It is compatible with all types of Portland cement.

RECOMMENDATIONS FOR USE

Fluidcret G is a necessary additive for the preparation of concretes with high resistance to compression, for concretes exposed to atmospheric agents, as well as for concrete that will immerse into water.

INSTRUCTIONS FOR USE

- Fluidcret G is suitable for all types of Portland cement.
- An overdose can cause accelerated drying but does not affect the final strength of the concrete.
- If the material is frozen, turn the temperature to + 5 ° C and mix it until it is homogenized again.

STORAGE

18 months after production date, if the product is stored in original and unopened packaging, at temperatures between +5°C and +35°C and protected from direct exposure to sun and frost.

TECHNICAL DATA

Form:	Liquid
Colour:	Brown
Density:	1,05 Kg/l
pH:	9
Solid content:	32%
Dosage:	0.5% - 1% in relation to cements
Viscosity:	50 MPa.s
Alkaliniteti:	2%

PACKAGING

5 Kg / 20 Kg / 100 Kg plastic bottles

DOSAGE

0.3 - 0.5 Kg per 100 Kg cement.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

