

PICASSO J'ADORE



DESCRIPTION

Emulsion paint of excellent quality for general interior use

CHARACTERISTICS

- Great hiding power
- Great whiteness
- Smooth matt finish
- Very good working and leveling properties
- Strong adhesion and quick drying
- Ammonia free
- Economic solution for frequent painting and freshening up

RECOMMENDATIONS FOR USE

Interior surfaces of plaster, concrete, brick, wood, stucco, gypsum board, plastic etc.

TECHNICAL DATA

Resin	Acrylic Copolymer
Density (white):	1,60±0,02 gr/ml
Production viscosity (white):	110±5 KU 23°C
Storage viscosity (white):	110±7 KU 23°C
Spreading rate:	Up to 9m²/lit for each coat
Dry through(white):	20±10 minutes
Recoating time (white):	50±10 minutes
Dry through (shades):	30±10 minutes
Recoating time (shades):	2±½ hours (Drying and recoating time may be prolonged under conditions of low temperature and high relative humidity)
Shades:	Available in white and in thousands of shades via the deutschcolor tinting system (dcts). It can be tinted also with dc basics emulsion colorants.
VOC (Volatile Organic Compounds):	Limit value for this product category α/a "interior matt walls and ceilings (gloss<25@60°)": 30g/l (2010). The product contains max. 29G/l.

APPLICATION PROCEDURE

Application method: Brush, roller, airless spray

Diluent: Water

Water demand: 10-15% v/v

Surfaces must be clean, dry and free from all defective and poorly adhering material, dust, dirt, oils and salts.

Hansa Spachtel/ Spachtel Elastisch: For filling, where ever is necessary

Macht Haftgrund: Thinned 100-300%, for sound surfaces without coherence problems

Macht Tiefgrund Wasser: Thinned up to 100%, for very porous surfaces or surfaces already coated with lime or low quality chalky paints

Picasso J'adore: Directly, for the refinishing of sound surfaces Picasso J'adore is applied in 2 coats. Tools are cleaned immediately after the application with soap and water.

CONSUMPTION

9 - 10 m² / lt (two coats)

PACKAGING

3lt / 9lt / 15lt plastic buckets

STORAGE

36 months, provided the cans remain closed and in normal storing conditions.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- On fresh concrete surfaces it is recommended to apply the product at least after 30-40 days.
- It is recommended to avoid the application of the product at temperatures below 5°C.
- Picasso J'adore bases are ONLY used for the production of colored shades via DCTS. They should not be applied without the special colorants.

