

BETON FARBE



DESCRIPTION

Beton Farbe is a solvent-based paint for surface coating.

PRODUCT CHARACTERISTICS

- Solvent-based
- Strong adhesion
- Deep surface penetration
- High mechanical resistance
- Excellent coverage

RECOMMENDED USES

Beton Farbe is a solvent-based paint designed for coating porous surfaces such as concrete, asphalt, and porous stones, characterized by very strong adhesion. It has good resistance to weather conditions and abrasion, fast drying, and hardness. It offers excellent penetration properties on all types of surfaces where it is applied and is easy to use. Thanks to its high mechanical resistance, it forms a highly protective layer over the applied surface. It is distinguished by high resistance to fading, color loss, or detachment from the surface.

TECHNICAL CHARACTERISTICS

Base:	Solvent
Density:	1,60±0,05 gr/ml
Product viscosity (white):	85±5 KU 23°C
Storage viscosity (white):	85±5 KU 23°C
Spreading rate:	3-4 m ² /liter
Touch dry:	10-15 minutes
Fully dry:	30-40 hours
Recoat time:	2-4 hours (Drying and recoating time may be extended under low temperature and high relative humidity conditions.)
Shades:	Available in white and various colors according to the RAL chart.

APPLICATION INSTRUCTIONS

Application method: Road marking applicator, roller, brush or spray
Thinner: Spritz Sol XT
Dilution: Can be diluted 5–10% v/v with Spritz Sol XT.
Surfaces must be clean, dry, and smooth, free from dust and grease.

APPLICATION

Beton Farbe is applied in one or to coats.
The recommended application temperature is from 10 °C to 35 °C.
Clean tools with Spritz Sol XT immediately after use.

PACKAGING

0.75 liter

CONSUMPTION

3-4 m²/liter

STORAGE

18 months, if stored in a sealed container and under normal storage conditions.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep the product out of reach of children. If swallowed, seek medical advice immediately and show the container or label. Do not dispose of the product into drains or water channels.

